

TECHNICAL DATA STANDARD PANEL

MODEL	DIMENSIONS (mm)								INPUT POWER (kW)		GAS CONSUMPTION (MAX)		
	WIDTH	LENGHT	THICKN ESS	WEIGHT (kg)	VOLTAGE SUPPLY	PRE - HEATING ELECTRICAL POWER	PRE - HEATING TIME	GAS SUPPLY	MAX kW	MAX BTU/HR	GPL (g/h)	NATURAL GAS (m3/h)	CONTROL DEVICE
8.20	210	510	4,8	3,5	230V	400 W	15'	NG - GPL	2,2	1,3	190	0,22	BIMETALLIC VALVE/ ELECTTROC THERMOSTAT
10.20	260	510	4,8	3,6	230V	400 W	15'	NG - GPL	2,7	1,6	235	0,27	BIMETALLIC VALVE/ ELECTTROC THERMOSTAT
16.20	410	510	4,8	5	230V	600 W	15'	NG - GPL	4,3	14500	380	0,41	BIMETALLIC VALVE/ ELECTTROC THERMOSTAT
16.20	410	510	4,8	5	230V	1100 W	12'	NG - GPL	4,3	14500	380	0,41	BIMETALLIC VALVE/ ELECTTROC THERMOSTAT